


SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Paul H. Gesswein & Co., Inc.
 201 Hancock Ave., Bridgeport, CT 06605
 Phone: 203-366-5400, FAX: 203-366-3953
 email: info@gesswein.com, www.gesswein.com

Emergency phone number: CHEMTELL - 800-255-3924



Product Name: Norton® Hard Arkansas Files
Product Number: 3700130, 3700330, 3700430,
 3701130, 3701330, 3701430, 3708230, 3708330,
 3708430, 3708530, 3700630, 3708730, 3708130

HMIS	
Health Hazard	1
Fire Hazard	0
Reactivity	1
Personal Protection	X

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Crystalline Silica, Quartz	14808-60-7	> 99 by weight	238-878-4
Aluminum Oxide, Non-fibrous	1344-28-1	< 1 by weight	215-691-6
Titanium Oxide	13463-67-7	< 1 by weight	236-675-5
Iron (III) oxide	1309-37-1	< 1 by weight	
Proprietary	No Data	5 - 10 by weight	

SECTION 3 : HAZARDS IDENTIFICATION
Potential Health Effects:

- Eye:** Dust may cause slight irritation.
- Skin:** Dust from this product may cause temporary mechanical irritation.
- Inhalation:** Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract.
- Ingestion:** Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.

Chronic Health Effects: Chronic health effects are not expected as long as good hygiene and proper safety precautions are practiced.

SECTION 4 : FIRST AID MEASURES

- Eye Contact:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get medical attention, if irritation or symptoms of overexposure persists.
- Skin Contact:** Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Inhalation:** If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist, get medical attention.
- Ingestion:** Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician.
- Note to Physicians:** No information available.

SECTION 5 : FIRE FIGHTING MEASURES

Flammable Properties:	Non Flammable.
Flash Point:	Does not apply.
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not available.
Upper Flammable/Explosive Limit:	Not available.
Extinguishing Media:	Use any extinguishing media appropriate for the surrounding fires.
Unsuitable Media:	None.
Protective Equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA Ratings:

NFPA Health:	0
NFPA Flammability:	0
NFPA Reactivity:	1
NFPA Other:	

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Methods for containment:	Containment of this material should not be necessary.
Methods for cleanup:	Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Dispose of in accordance with Local, State, Federal and Provincial regulations.

SECTION 7 : HANDLING and STORAGE

Handling:	<p>Always HANDLE AND STORE wheels in a CAREFUL manner.</p> <p>Always VISUALLY INSPECT all wheels before mounting.</p> <p>Always CHECK MACHINE SPEED against the established maximum safe operating speed MARKED ON THE WHEEL.</p> <p>Always CHECK MOUNTING FLANGES for equal and correct diameter.</p> <p>Always USE MOUNTING BLOTTERS.</p> <p>Always be sure WORK REST is properly adjusted.</p> <p>Always USE A SAFETY GUARD covering at least one-half of the grinding wheel.</p> <p>Always allow NEWLY MOUNTED WHEELS to run at operating speed, with guard in place, for at least one minute before grinding.</p> <p>Always TURN OFF COOLANT before stopping wheel to avoid creating an out-of-balance wheel.</p>
Storage:	No special storage conditions required.
Hygiene Practices:	Wear suitable gloves and eye/face protection.

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	General dilution ventilation and/or local exhaust ventilation should be provided as necessary to maintain exposures below occupational exposure limits.
Eye/Face Protection:	Always WEAR SAFETY GLASSES or some type of eye protection when grinding.
Skin Protection Description:	Protective gloves. Long sleeved shirt and long pants.
Respiratory Protection:	When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.
Other Protective:	Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).
General Hygiene Considerations:	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

EXPOSURE GUIDELINES

Ingredient	Guideline OSHA	Guideline ACGIH	Quebec Canada	Ontario Canada	Alberta Canada
Crystalline Silica, Quartz		TLV-TWA: 0.025 mg/m3 Respirable fraction (R)	VEMP-TWA: 0.1 mg/m3 Respirable fraction (R)	OEL-TWAEV: 0.05 mg/m3 Respirable fraction (R)	OEL-TWA: 0.1 mg/m3 Respirable fraction (R)
Aluminum Oxide, Non-fibrous	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)	TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)	OEL-TWA: 10 mg/m3
Titanium Oxide		TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)	OEL-TWA: 10 mg/m3 Total particulate/dust (T)
Ingredient	Mexico	British Columbia Canada			

Crystalline Silica, Quartz	LMPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 0.025 mg/m3 Respirable fraction (R)		
Aluminum Oxide, Non-fibrous	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T)		
Titanium Oxide	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-TWA: 3 mg/m3 Respirable fraction (R)		

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Solid article.
 Odor: Odorless.
 Flash Point: Does not apply.
 Auto Ignition Temperature: Not determined.

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.
 Hazardous Polymerization: Hazardous polymerization does not occur.
 Special Decomposition Products: In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the grinding wheel components. Coolants may produce other decomposition products.

SECTION 11 : TOXICOLOGICAL INFORMATION

Acute Toxicity: This product has not been tested for its toxicity.

Carcinogens:						
	ACGIH	NIOSH	OSHA	IARC	NTP	
Aluminum Oxide, Non-fibrous	A4 Not Classifiable as a Human Carcinogen	No Data	No Data	No Data	No Data	

Crystalline Silica, Quartz :

RTECS Number: VV7330000

Aluminum Oxide, Non-fibrous :

RTECS Number: BD1200000

Inhalation: Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS)

Titanium Oxide :

RTECS Number: XR2275000

Skin: Skin - Human Standard Draize test. : 300 ug/3D-I - [mild] (RTECS)

Inhalation: Inhalation - Rat TCLo - Lowest published toxic concentration: 1 mg/kg - [Lungs, Thorax, or Respiration - Other changes Biochemical - Metabolism (Intermediary) - Effect on inflammation or mediation of inflammation] (RTECS)

Ingestion: Oral - Rodent rat TDLo - Lowest published toxic dose: 60 gm/kg - [Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Other changes] (RTECS)

Proprietary :

RTECS Number: VW0450000

SECTION 12 : ECOLOGICAL INFORMATION

Biodegradation: Resin bonded materials demonstrate similar degradation rates as Phenolic plastics.

SECTION 13 : DISPOSAL CONSIDERATIONS

Waste Disposal: Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Not regulated as hazardous material for transportation.

DOT UN Number: Not regulated as hazardous material for transportation.

IATA Shipping Name: Not regulated as hazardous material for transportation.

Canadian Shipping Name: This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

SECTION 15 : REGULATORY INFORMATION

Crystalline Silica, Quartz :

TSCA Inventory Status: Listed

Massachusetts: Listed

Pennsylvania: Listed

Canada DSL: Listed

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.1406(1491)

EC Number: 238-878-4

Aluminum Oxide, Non-fibrous :

TSCA Inventory Status: Listed

EINECS Number: 262-373-8

New Jersey: Listed: NJ Hazardous List; Substance Number: 2891

Massachusetts: Listed

Pennsylvania: Listed

Minnesota: Listed

Illinois: No Data

Rhode Island: Listed

Canada DSL: Listed

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

EC Number: 215-691-6

Titanium Oxide :

TSCA Inventory Status: Listed

New Jersey: No Data

Massachusetts: Listed

Pennsylvania: Listed

Canada DSL: Listed

EC Number: 236-675-5

Iron (III) oxide :

TSCA Inventory Status: Listed

Canada DSL: Listed

SECTION 16 : ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 1

HMIS Fire Hazard: 0

HMIS Reactivity: 1

HMIS Personal Protection: X

SDS Creation Date: July 23, 2013

SDS Revision Date: July 23, 2013